

# AES67, Ravenna, SMPTE ST-2110 PCIe SOUND CARD

## Smart and ultra versatile

Open new possibilities with the PCIe ALP-AES67 audio interface: its **low-profile form-factor** design matches all PCs and servers to address applications requiring robust AES67 connectivity. Its **fanless design** reduces consumption for durability and sustainability.


The card's connectivity, combined with 64 channels of playback and 64 recording channels to/from an **AES67 / Ravenna / SMPTE ST-2110 network**,

reaches beyond the usual applications to go one step further. ALP-AES67 operates under **Windows or Linux** environments to address various applications. Built on the same reliable and stable architecture as all ALP-X cards, **ALP-AES67 is the perfect match for mission-critical applications where audio is key**: its versatility works wonders in broadcast, public safety, medical, transportation, or countless industry markets.

Low profile PCIe.  
Fanless design

Works under Windows  
and Linux  
64 DAW channels

2 or 4 Eth ports for  
redundancy (ST 2022-07) and  
switching



Compliant with AES67,  
Ravenna, and  
SMPTE ST 2110-30

PTP Grand Master  
or PTP slave

Management via network:  
WEB GUI, Aneman,  
MTDiscovery  
NMOS IS=04 & IS=05

## KEY FEATURES



### Secure content delivery & ingest:

HW-based permanence of  
service whatever the  
applications running on the  
host PC



### Same latency as Digital audio:

Sub-millisecond round trip  
latency



### Seamless migration to IP:

High density, ultra-low  
latency and phase accurate  
AoIP / PCI bridge



### Ensure interoperability:

full compliance with AES67,  
RAVENNA, SMPTE ST-2110  
& ST-2022-7



**Low Profile**  
**2 Eth ports**



**Low Profile**  
**4 Eth ports**



**Full-height Profile**  
**4 Eth ports**

## 1 FORMAT

### Bus

PCI Express™ x1  
(x2, x4, x8, x16 compatible)

### Form Factor

Low profile PCIe

Full-height PCIe (with the provided  
additional full-height bracket)

### Dimensions

L: 168 mm x H: 69 mm x l: 20 mm  
L: 6.6 inch; H: 2.7 inch; l: 0.8 inch

L: 168 mm x H: 99 mm x l: 20 mm  
L: 6.6 inch; H: 3.9 inch; l: 0.8 inch

## 2 DRIVERS

### Supported OS

Windows (as of Windows 10 20H2, Server 2019)  
Linux: UBUNTU as of ver. 20, DEBIAN as of  
ver.10, CentOS as of ver.9

### Drivers

Windows: Asio, Wasapi/DirectSound

Linux: Alsa

### One Driver Package

Multi-application and multi-card  
API available to access the  
parameters

## 3 CONTROL PANEL

### Digigram ALP-X ASIO Settings (Windows)

- Asio Control Panel: up to 8 ALP-X cards
- Select I/Os used through Asio  
(others can be used through Wasapi)

### Digigram ALP-X Manager (Windows)

- One unified control panel for the whole ALP-X range
- Manages up to 8 ALP-X cards
- Vu-meters, clock frequency
- Firmware update



## 4 SPECIFICATIONS

### Network connectivity

- Configuration with two network ports  
2 x Gbps Eth ports that can be used in redundancy mode  
(ST 2022-7), or in switching mode
- Configuration with four network ports  
4 Eth ports on the full-height bracket, or 2 Eth ports on  
each low-profile bracket
  - Switch mode (the 4 ports are identical)
  - ST 2022-7 mode: 2 pairs of redundant ports

### Input and output channels

- 64 x 64 channels at 44.1kHz and 48 kHz
- 32 x 32 channels at 88.2 kHz and 96 kHz
- 16 x 16 channels at 176.4 kHz and 192 kHz

### Audio flows

- Maximum 64 input and 64 output streams

### Buffering

- Up to 2000 samples per channel (41.7ms at 48 kHz)

### AoIP compliance

- AES67, Ravenna
- SMPTE ST 2110-30 Level A,B, C
- SMPTE ST 2022-7 (Class A,B,C,D)
- SAP for streams announcement for compatibility with Dante  
products set to AES67 mode

### Sample format

- PCM 16, 24, 32 bits

### Management

- WEB GUI, Aneman & MTDDiscovery (Merging Technologies)
- NMOS IS=04 & IS=05  
(Discovery & Registration, Connection management)